

5 x 8 Single Axle

Standard on the 5 x 8:

- BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- 2" COUPLER
- 5' INTERIOR HEIGHT
- TONGUE JACK
- SPRING IDLER AXLE
- 4 WAY ELECTRICAL PLUG
- 24" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 24" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 12" STONEGUARD

5 x 10 Single Axle

Standard on the 5 x 10:

- BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- 2" COUPLER
- 5' INTERIOR HEIGHT
- TONGUE JACK
- SPRING IDLER AXLE
- 4 WAY ELECTRICAL PLUG
- 24" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 24" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 12" STONEGUARD

6 X 10 Single Axle

Standard on the 6 x 10:

- ST205 15" BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- 2" COUPLER
- 6' INTERIOR HEIGHT
- 2000 LB TONGUE JACK
- IDLER LEAF SPRING AXLE
- 4 WAY ELECTRICAL PLUG
- 24" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 24" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 18" STONEGUARD

6 X 12 Single Axle

Standard on the 6 x 12:

- ST205 15" BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- 2" COUPLER
- 6' INTERIOR HEIGHT
- 2000 LB TONGUE JACK
- IDLER LEAF SPRING AXLE
- 4 WAY ELECTRICAL PLUG
- 24" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 24" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 18" STONEGUARD

6 X 14 Single Axle

Standard on the 6 x 14:

- ST205 15" BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- 2" COUPLER
- 6' INTERIOR HEIGHT
- 2000 LB TONGUE JACK
- IDLER LEAF SPRING AXLE
- 4 WAY ELECTRICAL PLUG
- 24" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 24" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 18" STONEGUARD

7 x 10 Single Axle

Standard on the 7 x 10:

- ST205 15" BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- COUPLER
- 6' INTERIOR HEIGHT
- 2000 LB TONGUE JACK
- 3500 LB IDLER LEAF SPRING
- 4 WAY ELECTRICAL PLUG
- 16" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 16" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 18" STONEGUARD

7 x 12 Single Axle

Standard on the 7 x 12:

- ST205 15" BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- COUPLER
- 6' INTERIOR HEIGHT
- 2000 LB TONGUE JACK
- 3500 LB IDLER LEAF SPRING
- 4 WAY ELECTRICAL PLUG
- 16" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 16" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 18" STONEGUARD

ALL TRAILERS COME STANDARD WITH A 12 VOLT INTERIOR LIGHT WITH SWITCH, NON POWERED ROOF VENT, AND THERMACOOL CEILING.

****NO EXTRA CHARGE FOR V-NOSE, STRAIGHT FRONT, REAR DOOR.****