



7 Ton Tagalong Workhorse Series

Pierced Frame

• G.V.W.R. - 14,000 #	• Axles - 2 Dexter 7,000 # single wheel electric brake axles
• G.A.W.R.(Each Axle) - 7,000 #	• Suspension-Multi-leaf spring w/equalizer
• Coupler - 3 position adjustable	• Tires - ST 235/ 80R 16" Load Range E
• Safety Chain-3/8" grade 43 with hooks	• Wheel - 6.75 x 16" 8 bolt White Spoke
• Jacks - dual 10,000 # drop leg side crank	• Deck - 2" pressure treated pine
• Frame -12" I-beam	• Lights - D.O.T. stop, tail, turn, and clearance
• Crossmembers -3" structural channel on 16"centers with pierced frame construction	• Elec. Plug - 7-way RV
• Side rails -6"channel w/stake pockets/rub rails	• Paint - high solids acrylic enamel

Standard Features

Optional Features

• 16" white spoke	• Center pop-up dovetail with gas spring assist.
• Sealed modular wiring harness	• Double 2-speed jacks
• E-Z lube brake axles	• Electric over hydraulic
• Electric breakaway	• No dovetail & ramps
• 5' Self cleaning dovetail	• Anti twist pipes
• Deck level ramps	
• Rubber mt. lights	
• Spare tire mount	
• Keyed security lock for storage box	

Dimensions

Weight / Length	A	B	C	D	E	Dove
5,550Lbs / 25'	300"	178.75"	68"	34"	102"	60"
5,700Lbs / 29'	348"	202.75"	68"	34"	102"	60"

