



LST Utility Series

• G.V.W.R. -7,000 #	• Axles-2-3,500# Brake axles E-Z lube
• G.A.W.R.(Each Axle) -3,500 #	• Suspension - Multi-leaf spring with equalizer
• Coupler - 2"	• Tire - 205-75-15" load range C
• Safety chains 8/0 grade 30 with hooks	• Wheel - 15" 5 bolt white spoke
• Jack - top wind	• Deck - Pressure treated pine
• Frame - 2"x3"x3/16"	• Gate - 48" fold down
• Crossmembers 3" x 2" x 3/16 angle	• Lights - D.O.T. stop, tail, and turn
• Fenders - 9"x72" treadplate with backs	• Elec. Plug - 7-way RV
• Deck Height 20"	• Finish - High solids acrylic enamel

Standard Features Optional Features

• 15" white spoke rims	• Higher sides
• Pressure treated decking	• Slatted metal sides
• Light protector	• Swing up jack
• Electric breakaway	• Wrap tongue
• E-Z Lube brake axles	• 6' Wide Double Fold gate
• 7 way RV plug	• 7' Wide Double Fold gate
• Gate length 48" Gas Springs	• Double split gate

Dimensions

Weight / Length	A	B	C	D	E
1,290Lbs / 10'	120"	81.5"	38.5"	20"	76"
1,380Lbs / 12'	144"	93"	38.5"	20"	76"
1,470Lbs / 14'	168"	104"	38.5"	20"	76"
1,560Lbs / 16'	192"	114"	38.5"	20"	76"
1,650Lbs / 18'	216"	124"	38.5"	20"	76"
1,740Lbs / 20'	240"	134"	38.5"	20"	76"

