



6 T Equipment Pipe Rail Series

• G.V.W.R.-12,000 #	• Axles - 2-6,000 # cambered brake axles
• G.A.W.R.(Each Axle) - 6,000 #	• Suspension - Slipper spring with equalizer
• Coupler - 2 - 5/16" adjustable	• Tires - ST 235 / 80R 16" load range D
• Safety Chain - 3/8" grade 43 with hooks	• Wheel -16" 8 bolt white spoke
• Jack -10,000 # drop leg	• Deck - 2" pressure treated pine
• Frame - 5" angle w/ H.D.2 1/2" pipe rail	• Lights - D.O.T. stop, tail, turn, and clearance
• Crossmembers - 3" channel	• Elec. plug - 7-way RV
• Fenders - 10"x72" diamond plate with backs	• Paint - high solids acrylic enamel
• Tongue - 6" channel wrap around	• 4' Ramps
• Bed width - 81"	• Sealed modular wiring harness

Standard Features Optional Features

• 16" white spoke	• Steel deck
• Pressure treated decking	• Double-split gate w/ springs
• Light protectors	• Self cleaning dovetail
• Electric breakaway	• D-Rings
• E-Z Lube axles	• 5' ramps

Dimensions

Weight / Length	A	B	C	D	E
3,200Lbs / 12'	144"	95.5"	43"	25.5"	82"
3,350Lbs / 14'	168"	107.5"	43"	25.5"	82"
3,500Lbs / 16'	192"	119.5"	43"	25.5"	82"
3,650Lbs / 18'	216"	131.5"	43"	25.5"	82"
3,800Lbs / 20'	240"	143.5"	43"	25.5"	82"
3,950Lbs / 22'	264"	155.5"	43"	25.5"	82"
4,000 Lbs / 24'	288"	167.5"	43"	25.5"	82"

