### 6 x 12 Tandem Axle

# Standard on the 6 x 12:

- ST205 15" BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- 2 5/16" COUPLER
- 6' INTERIOR HEIGHT
- 2000 LB TONGUE JACK
- 3500 TANDEM BRAKE AXLES WITH SPRING SUSPENSION
- EZ HUB LUBE AXLE
- 7 WAY ELECTRICAL PLUG
- 24" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 24" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 18" STONEGUARD

# 6 x 14 Tandem Axle

# Standard on the 6 x 14:

- ST205 15" BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- 2 5/16" COUPLER
- 6' INTERIOR HEIGHT
- 2000 LB TONGUE JACK
- 3500 TANDEM BRAKE AXLES WITH SPRING SUSPENSION
- EZ HUB LUBE AXLE
- 7 WAY ELECTRICAL PLUG
- 24" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 24" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 18" STONEGUARD

#### 6 x 16 Tandem Axle

# Standard on the 6 x 16:

- ST205 15" BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- 2 5/16" COUPLER
- 6' INTERIOR HEIGHT
- 2000 LB TONGUE JACK
- 3500 TANDEM BRAKE AXLES WITH SPRING SUSPENSION
- EZ HUB LUBE AXLE
- 7 WAY ELECTRICAL PLUG
- 24" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 24" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 18" STONEGUARD

# 7 x 12 Tandem Axle

# Standard on the 7 x 12:

- ST205 15" BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- 2 5/16" COUPLER
- 6' INTERIOR HEIGHT
- 2000 LB TONGUE JACK
- 3500 TANDEM BRAKE AXLES WITH SPRING SUSPENSION
- EZ HUB LUBE AXLE
- 7 WAY ELECTRICAL PLUG
- 16" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 16" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 18" STONEGUARD

### 7 x 14 Tandem Axle

# Standard on the 7 x 14:

- ST205 15" BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- 2 5/16" COUPLER
- 6' INTERIOR HEIGHT
- 2000 LB TONGUE JACK
- 3500 TANDEM BRAKE AXLES WITH SPRING SUSPENSION
- EZ HUB LUBE AXLE
- 7 WAY ELECTRICAL PLUG
- 16" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 16" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 18" STONEGUARD

### 7 x 16 Tandem Axle

# Standard on the 7 x 16:

- ST205 15" BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- 2 5/16" COUPLER
- 6' INTERIOR HEIGHT
- 2000 LB TONGUE JACK
- 3500 TANDEM BRAKE AXLES WITH SPRING SUSPENSION
- EZ HUB LUBE AXLE
- 7 WAY ELECTRICAL PLUG
- 16" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 16" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 18" STONEGUARD

### 7 x 18 Tandem Axle

# Standard on the 7 x 18:

- ST205 15" BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- 2 5/16" COUPLER
- 6' INTERIOR HEIGHT
- 2000 LB TONGUE JACK
- 3500 TANDEM BRAKE AXLES WITH SPRING SUSPENSION
- EZ HUB LUBE AXLE
- 7 WAY ELECTRICAL PLUG
- 16" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 16" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 18" STONEGUARD

### 7 x 20 Tandem Axle

# Standard on the 7 x 20:

- ST205 15" BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- 2 5/16" COUPLER
- 6' INTERIOR HEIGHT
- 2000 LB TONGUE JACK
- 3500 TANDEM BRAKE AXLES WITH SPRING SUSPENSION
- EZ HUB LUBE AXLE
- 7 WAY ELECTRICAL PLUG
- 16" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 16" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 18" STONEGUARD

#### 8 x 16 Tandem Axle

### Standard on the 8 x 16:

- ST205 15" BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- 2 5/16" COUPLER
- 6 1/2' INTERIOR HEIGHT
- 2000 LB TONGUE JACK
- 3500 TANDEM BRAKE AXLES WITH SPRING SUSPENSION
- EZ HUB LUBE AXLE
- 7 WAY ELECTRICAL PLUG
- 16" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 16" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 24" STONEGUARD

### 8 x 20 Tandem Axle

# Standard on the 8 x 20:

- ST205 15" BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- 2 5/16" COUPLER
- 6 1/2' INTERIOR HEIGHT
- 2000 LB TONGUE JACK
- 3500 TANDEM BRAKE AXLES WITH SPRING SUSPENSION
- EZ HUB LUBE AXLE
- 7 WAY ELECTRICAL PLUG
- 16" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 16" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 24" STONEGUARD

### 8 x 24 Tandem Axle

# Standard on the 8 x 24:

- ST205 15" BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- 2 5/16" COUPLER
- 6 1/2' INTERIOR HEIGHT
- 2000 LB TONGUE JACK
- 3500 TANDEM BRAKE AXLES WITH SPRING SUSPENSION
- EZ HUB LUBE AXLE
- 7 WAY ELECTRICAL PLUG
- 16" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 16" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 24" STONEGUARD

### 8 x 28 Tandem Axle

# Standard on the 8 x 28:

- ST205 15" BIAS PLY TIRE/WHEELS
- SCREWED EXTERIOR
- 3/8" PLYWOOD WALLS
- 3/4" PLYWOOD FLOOR
- .024" ALUMINUM EXTERIOR W/ WHITE ENAMEL
- 2 5/16" COUPLER
- 6 1/2' INTERIOR HEIGHT
- 2000 LB TONGUE JACK
- 3500 TANDEM BRAKE AXLES WITH SPRING SUSPENSION
- EZ HUB LUBE AXLE
- 7 WAY ELECTRICAL PLUG
- 16" O.C. WALL STUDS/TUBING
- 24" O.C. ROOF MEMBERS/TUBING
- 16" O.C. FLOOR CROSS MEMBERS
- GALVALUME ROOF
- 24" STONEGUARD

\*ALL TRAILERS COME STANDARD WITH A 12 VOLT INTERIOR LIGHT WITHSWITCH, NON POWERED ROOF VENT, AND THERMACOOL CEILING.\*

\*\*NO EXTRA CHARGE FOR V-NOSE, STRAIGHT FRONT, REAR DOOR.\*\*