

HD LOW PROFILE DECKOVER WITH HYDRAULIC BEAVERTAIL









HD Hydraulic Ram

Protected Pump

Self-Retained Latch Pin

110 Volt Battery Charger



SURE-TRAC DIFFERENCE

Pierced I-Beam Frame HD I-Beam Gooseneck All LED Lights Everlink™ - High-Performance Wiring Harness Sealed Brake Connections Undercoated Main Frame

FEATURES

Pressure-Treated 2 x 6 Decking 110 Volt Battery Charger

Oil Filled Hubs (Tandem Dual) 16" Radial Tires Slipper Springs

Dual HD 12K Drop Leg Jacks Toolbox Between Uprights on Gooseneck HD 5" Bore Twin Lift Cylinders in Beavertail Spare Tire Carrier HD Stake Pockets and Rub Rail (10) HD D-Rings Chain Spools Side Steps HD Bulkhead (New)

OPTIONS

Brake Options Battery Charger Spare Tire Color Options Contact Your Local Dealer for More Options







Wholesale Dealer | SMART - CONFIDENT - PROVEN

2018 SPECIFICATIONS FOR GOOSENECK HD LOW PROFILE DECKOVER WITH HYDRAULIC BEAVERTAIL

		8.5 X 20 + 10	
GVWR (lbs)	22500	25900	32000
GAWR (lbs/axle)	10000	12000	16000
Curb Weight	6520	6680	7580
Payload	15980	19220	24420
Main Frame	W12 x 19#/ft., I-Beam W12 x 22#/ft. I-Beam		
Side Rails	6" C-Channel		
Cross Members	3" C-Channel (16" On-Center) 3" Channel (12" On-Cente		
Beaver Tail	Wood Deck		
Gooseneck Coupler	Adjustable 2-5/16 Ball		
Jack	Dual HD 12K Jacks with Toolbox		
Axles	Oil Bath Bearing		
Suspension	Slipper Leaf Spring		
Tires	235/80R16 LRE		215/75R 17.5
Wheels	16"		17.5"
	Grey		
Decking	2" Pressure Treated Pine		
Lights	All LED Lights		
Electric Plug	7 Pole RV Molded Flat Blade		
Finish	Primed and Enamel Painted Exterior, Undercoated Main Frame		
Overall Length	497"		
Deck Height	32"		
Coupler Height	Adjustable 31" - 39-3/4"		
Beavertail Payload	5000 lbs		
Beavertail Lifting Capacity	8000 lbs (Center of Tail)		
Load Angle	15 Degrees		





