



D6TLP Dump Series

• G.V.W.R.-12,000 #	• Axles - 2-6,000 # cambered brake axles
• G.A.W.R.(Each Axle) - 6,000 #	• Suspension - slipper spring with equalizer
• Coupler - 2-5/16" adjustable	• Tires - ST235/80R/16" load range E
• Safety Chain - 3/8" grade 43 with hooks	• Wheel -16" 8 bolt white spoke
• Jack -7,000 # drop leg	• Deck - 12 ga. smooth steel
• Frame - all tubing construction	• Lights - D.O.T. stop, tail, turn, and clearance
• Fenders - 10"x72" diamond plate	• Elec. Plug - 7-way RV
• Tongue - 6" channel wrap around	• Paint - High solids acrylic enamel
• 12 volt front mounted self contained hydraulic pump system	• Stake pockets on sides
• 2-way side and top hinge	• Sides-24 " 14 ga. smooth steel
	• Ramps with track

Standard Features

Optional Features

• 16" white spoke wheels	• Higher sides
• Cable remote for dump	• Double barn doors
• Light protectors	• Tarp system
• Electric breakaway	• Charger
• E-Z Lube axles	• Gooseneck hitch
• Hydraulic scissor hoist	

Dimensions

Weight / Length	A	B	C	D	E	F
3,700Lbs / 10'	120"	78"	45"	29"	76"	17"
4,000Lbs / 12'	144"	90"	45"	29"	76"	17"

