



10 Ton Gooseneck Series

• G.V.W.R. - 25,000 #	• Axles - 2 Dexter 10,000# dual wheel electric brake axles
• G.A.W.R.(Each Axle) - 10,000 #	• Suspension - Multi-leaf slipper spring with equalizer
• Coupler - 2 5/16" adjustable	• Wheel - 6.75 x 16" dual 8 bolt
• Safety Chain-3/8" grade 43 with hooks	• Tires - ST 235/80R "16" Load Range E
• Jack - 10,000 # drop leg	• Deck - 2" pressure treated pine
• Frame - 12" I-beam @ 16	• Lights - D.O.T. stop, tail, turn, and clearance
• Crossmembers -3" channel on 16" center	• Elec. Plug - 7-way RV
• Side rails - 6" channel with stake pockets and rub rails	• Paint - High solids acrylic enamel
• * Frame - 12" @ 19 I-beam 31' and up	

Standard Features

Optional Features

• 16" dual wheels	• Dual jacks
• Crossmembers on 16" centers	• Steel deck
• Sealed modular wiring harness	• Deck over neck
• Electric breakaway	• 12 ton capacity
• Oil bath axles	• Electric over hydraulic Brakes
• 5' dovetail	• Headache rack
• 5' ramps	• D-rings
• Rubber mt. lights	• Spring-loaded ramps
• Spare tire mt.	• 3rd ramp

Dimensions

Weight / Length	A	B	C	D	E
5,900Lbs / 21'	252"	150"	91"	37"	102"
6,200Lbs / 25'	300"	175"	91"	37"	102"
6,500Lbs / 29'	348"	209"	91"	37"	102"
6,800Lbs / *31'	372"	224"	91"	37"	102"
7,150Lbs / *33'	396"	242"	91"	37"	102"
7,450Lbs / *35'	420"	266"	91"	37"	102"
7,750Lbs / *40'	480"	336"	91"	37"	102"

