




HD LOW PROFILE BEAVERTAIL DECKOVER



HD Stake Pockets, Rub Rail and Chain Spool



Cross Trac Bracing



Slipper Spring Suspension
14K and Up



Side Step



Tube Constructed Bumper,
Enclosing All Wires for Full Protection



Shown with Optional Heavy-Duty I-Beam Gooseneck



Shown with Universal Full-Width Ramps (Option)



Also Available in a Flatbed Model



Pierced Frame for Lower Deck Height
and Undercoated Main Frame

SURE-TRAC DIFFERENCE

Pierced I-Beam Frame
Cross Trac Bracing
All LED Lights
Everlink™ - High-Performance Wiring Harness
Sealed Brake Connections
Undercoated Main Frame

FEATURES

Pressure-Treated 2 x 6 Decking

Oil Filled Hubs (Tandem Dual)
Slipper Springs
16" Radial Tires

HD 12K Dropleg Jack

Tube Constructed Bumper
Spare Tire Carrier
HD Stake Pockets and Rub Rail
(10) HD D-Rings
Chain Spools
Side Steps
HD Bulkhead (New)

OPTIONS

Gooseneck
Ramps
Decking
Spare Tire
Contact Your Local Dealer
for More Options



SMART - CONFIDENT - PROVEN

SURE-TRAC.COM

© 2018 Novae Corporation. All Rights Reserved.





Wholesale Dealer | **SMART - CONFIDENT - PROVEN**

2018 SPECIFICATIONS FOR HEAVY DUTY LOW PROFILE BEAVERTAIL DECKOVER

8.5 X 20 + 5						
GVWR (lbs)		15000	17600	22500	25900	32000
GAWR (lbs/axle)		7000	8000	10000	12000	16000
Curb Weight	Bumper Pull	4640	4740	5540	5840	6210
	Gooseneck	4930	5030	5800	6100	6520
Payload	Bumper Pull	10360	12860	16960	20060	25790
	Gooseneck	10070	12570	16700	19800	25480
Main Frame		W12 x 14#/ft., I-Beam				W12 x 19#/ft Beam
Side Rails		5" C-Channel	6" C-Channel			
Cross Members		3" C-Channel (16" On-Center)				3" Channel (12" On-Center)
Beaver Tail		Self-Cleaning Cleats				
Coupler	Bumper Pull	Adjustable Pintle	Adjustable 4 Bolt Pintle			
	Gooseneck	Adjustable 2-5/16 Ball				
Jack	Bumper Pull	Center Mounted 12K Dropleg				
	Gooseneck	Dual HD 12K Jacks with Toolbox				
Axles		E-Z Lube Electric Brake		Oil Bath Bearing		
Suspension		Slipper Spring				
Tires		235/80R16 LRE	215/75R17.5	235/80R16 LRE		215/75R17.5 LRH
Wheels	16"		17.5"	16"		17.5"
	White Spoke		Grey	Grey		Grey
Decking		2" Pressure Treated Pine				
Lights		All LED Lights				
Electric Plug		7 Pole RV Molded Flat Blade				
Finish		Primed and Enamel Painted Exterior, Undercoated Main Frame				
Overall Length	Bumper Pull	378"	378"	378"	378"	378"
	Gooseneck	426"	426"	426"	426"	426"
Deck Height		32"	32"	32"	32"	32"
Coupler Height	Bumper Pull	Adjustable 21"-29"				
	Gooseneck	Adjustable 31" - 39-3/4"				
Ramps		HD Fabricated Fold Flat with Double Hinged spring assist				



SMART - CONFIDENT - PROVEN

SURE-TRAC.COM

© 2018 Novae Corporation. All Rights Reserved.

