



20 Ton Tagalong Commercial Series

Pierced Frame

• G.V.W.R. - 45,000 #	• Axles - 2 25,000 # dual wheel air brake axles with spring break
• G.A.W.R. (Each Axle) - 25,000 #	• Suspension - Heavy duty Hutch 9700
• Coupler -3 position pintle ring	• Tires -ST215/75R/17.5" load range H
• Safety Chain -7/16" grade 70 with hooks	• Wheel - 6.75 x 17.5" 8 bolt Hub-piloted disc
• Jack -25,000 # 2 speed landing gear	• Deck - 2" oak
• Frame -14" @ 26 # I-beam	• Lights - L.E.D. stop, tail, turn, and clearance
• Crossmembers -5" channel on 16" center	• Elec. Plug -7-way semi type
• Side rails - 8"channel with (10) D-rings	• Paint - high solids acrylic enamel
• EZ lift Ramps	

Standard Features

Optional Features

• ABS on one axle	• Paver option
• Sealed modular wiring harness	• Spare tire mount
• Internal to air and emergency relay valve	• 36" Wide Hyd Ramps
• Oil bath axles	• Wood-covered ramps
• 5' dovetail	• Anti twist pipe
• 5' ramps spring loaded	
• Locking tool box	
• Rubber mounted lights	
• EZ lift Ramps	

Dimensions

Weight / Length	A	B	C	D	E	Dove
9,300Lbs / 25'	300"	189.5"	69"	36.75"	102"	60"
9,500Lbs / 29'	348"	213.5"	69"	36.75"	102"	60"
9,700Lbs / 33'	396"	237.5"	69"	36.75"	102"	60"

