



5T Equipment Series

• G.V.W.R. - 9,950 #	• Axles - 2-5,200 # cambered brake axles
• G.A.W.R.(Each Axle) - 5,200 #	• Suspension - Multi-leaf spring with equalizer
• Coupler - 2"- 5/16 adjustable	• Tires - 225-75-15" load range D
• Safety Chain - 3/8" grade 43 with hooks	• Wheel -15 in. 6 bolt white spoke
• Jack -7,000 # drop leg	• Deck - 2 in. pressure treated pine
• Frame - 6" channel	• Lights - D.O.T. Stop, tail, turn, and clearance
• Crossmembers - 3" channel	• Elec. Plug - 7-way RV
• Fenders - 10"x72" diamond plate with backs	• Paint - High solids acrylic enamel
• Tongue - 6" channel wrap around	• Ramps - 5' fold down

Standard Features Optional Features

• 15" white spoke rims	• Side rails
• Pressure treated decking	• Steel deck
• Light protectors	• Double-split gate w/ springs
• Electric breakaway	• Surge Brakes
• E-Z Lube axles	• Steel floor

Dimensions

Weight / Length	A	B	C	D	E	Dove
2,575Lbs / 12'	144"	88"	46.5"	24"	82"	24"
2,625Lbs / 14'	168"	100"	46.5"	24"	82"	24"
2,675Lbs / 16'	192"	112"	46.5"	24"	82"	24"
2,725Lbs / 18'	216"	124"	46.5"	24"	82"	24"
2,775Lbs / 20'	240"	136"	46.5"	24"	82"	24"

