



## *10 Ton Tagalong Commercial Series*

### *Pierced Frame*

|                                            |                                                             |
|--------------------------------------------|-------------------------------------------------------------|
| • G.V.W.R. - 25,900 #                      | • Axles - 2 Dexter 10,000 # dual wheel electric brake axles |
| • G.A.W.R.(Each Axle) -10,000#             | • Suspension - multi-leaf slipper spring                    |
| • Coupler -3 position pintle ring          | • Tires - ST235/80R/16" load range E                        |
| • Safety Chain -3/8" grade 43 with hooks   | • Wheel - 6.75 x 16" dual 8 bolt                            |
| • Jack-10,000 # drop leg                   | • Deck - 2" pressure treated pine                           |
| • Frame -12" I-beam                        | • Lights - D.O.T. stop, tail, turn, and clearance           |
| • Crossmembers - 4" channel on 16" center  | • Elec. Plug 7-way RV                                       |
| • Side rails - 8"channel with (10) D-rings | • Paint - high solids acrylic enamel                        |
| • EZ lift Ramps                            |                                                             |

#### *Standard Features*

#### *Optional Features*

|                                 |                           |
|---------------------------------|---------------------------|
| • 16" dual wheels               | • Dual jacks              |
| • Crossmembers on 16" centers   | • Boxend tail             |
| • Sealed modular wiring harness | • Air brakes              |
| • Electric breakaway            | • 12 Ton capacity         |
| • Oil bath axle                 | • Electric over hydraulic |
| • 5' Dovetail woodcovered       | • Electric over hydraulic |
| • 5' Ramps spring loaded        | Disc Brakes               |
| • Locking tool box              | • Paver option            |
| • Rubber mounted lights         | • 36" Wide Hyd Ramps      |

#### *Dimensions*

| Weight / Length | A    | B      | C     | D   | E    | Dove |
|-----------------|------|--------|-------|-----|------|------|
| 6,900Lbs / 25'  | 300" | 190.5" | 68.5" | 34" | 102" | 60"  |
| 7,100Lbs / 29'  | 348" | 214.5" | 68.5" | 34" | 102" | 60"  |
| 7,300Lbs / 33'  | 396" | 238.5" | 68.5" | 34" | 102" | 60"  |

